
# GRD 100

Oil Coolers
**GR S/D Series**





## Gamma Oil Coolers


| Product Code | Type of Setting | Overall H | Fan diameter | Fan Power m3/h | M.R. dm3 | Power Consumpt. |
|---|---|---|---|---|---|---|
| RU0100640000 | UNCOVERED | 45 | - | - | 4,24 | - |
| RU0100640011 | 12V Suct. | 210 | 305 | 1839 | 4,24 | 16,5 A |
| RU0100640012 | 12V Blow. | 210 | 305 | 1736 | 4,24 | 14,9 A |
| RU0100640021 | 24V Suct. | 210 | 305 | 2161 | 4,24 | 10,3 A |
| RU0100640022 | 24V Blow. | 210 | 305 | 2050 | 4,24 | 9,1 A |
| RU0100640031 [*] | 230V-50/60Hz Suct. | 175 | 300 | 3745 | 4,24 | 1,55 A |
| RU0100640032 [*] | 230V-50/60Hz Blow. | 175 | 300 | 3745 | 4,24 | 1,55 A |
| RU0100640041 | 230/400V-50/60Hz 3FN Suct. | 175 | 300 | 3350 | 4,24 | 0,48 A |
| RU0100640042 | 230/400V-50/60Hz 3FN Blow. | 175 | 300 | 3350 | 4,24 | 0,48 A |
| RU0100640051 | Pred. Hydraulic. Suct. (Supp. G2) | 225 | 300 | 3080 | 4,24 | 0,41 kW |
| RU0100640052 | Pred. Hydraulic. Blow. (Supp. G2) | 225 | 300 | 3080 | 4,24 | 0,41 kW |

[ * ] In SINGLE PHASE models (*31/*32), ADJUSTABLE THERMOSTAT 0-90° on request.

## Technical Specification

| | |
|---|---|
| Minimum Range | Kw 9 : 10 lt |
| Maximum Range | Kw 18 : 65 lt |




*The overall dimensions and the technical characteristics are to be considered indicative, dealing with standarf products in constant evolution.*

RAAL ITALIA s.r.l. Via G. Finati, 53 - 44124 Ferrara (ITA) C.F./P.IVA 01650320383
Tel: (+39) 0532.773637 Fax: (+39) 0532.776476 www.raal.it mail:info@raal.it