
GRS 200

Oil Coolers
GR S/D Series




Gamma Oil Coolers


Product Code	Type of Setting	Overall H	Fan diameter	Fan Power m3/h	M.R. dm3	Power Consumpt.
RU0100670000	UNCOVERED	65	-	-	9,47	-
RU0100670011	12V Suct.	220	305	1839	9,47	16,5 A
RU0100670012	12V Blow.	220	305	1736	9,47	14,9 A
RU0100670021	24V Suct.	220	305	2161	9,47	10,3 A
RU0100670022	24V Blow.	220	305	2050	9,47	9,1 A
RU0100670031 [*]	230V-50/60Hz Suct.	180	300	3745	9,47	1,55 A
RU0100670032 [*]	230V-50/60Hz Blow.	180	300	3745	9,47	1,55 A
RU0100670041	230/400V-50/60Hz 3FN Suct.	180	300	3350	9,47	0,48 A
RU0100670042	230/400V-50/60Hz 3FN Blow.	180	300	3350	9,47	0,48 A
RU0100670051	Pred. Hydraulic. Suct. (Supp. G2)	235	300	3080	9,47	0,41 kW
RU0100670052	Pred. Hydraulic. Blow. (Supp. G2)	235	300	3080	9,47	0,41 kW

[*] In SINGLE PHASE models (*31/*32), ADJUSTABLE THERMOSTAT 0-90° on request.

Technical Specification

Minimum Range	Kw 16 : 60 lt
Maximum Range	Kw 27 : 160 lt





The overall dimensions and the technical characteristics are to be considered indicative, dealing with standarf products in constant evolution.

RAAL ITALIA s.r.l. Via G. Finati, 53 - 44124 Ferrara (ITA) C.F./P.IVA 01650320383
Tel: (+39) 0532.773637 Fax: (+39) 0532.776476 www.raal.it mail:info@raal.it