
GRS 300

Oil Coolers
GR S/D Series




Gamma Oil Coolers


Product Code	Type of Setting	Overall H	Fan diameter	Fan Power m3/h	M.R. dm3	Power Consumpt.
RU0100690000	UNCOVERED	65	-	-	15,38	-
RU0100690011	12V Suct.	230	385	2212	15,38	16,0 A
RU0100690012	12V Blow.	230	385	2412	15,38	16,2 A
RU0100690021	24V Suct.	230	385	2577	15,38	9,3 A
RU0100690022	24V Blow.	230	385	2609	15,38	9,0 A
RU0100690031 [*]	230V-50/60Hz Suct.	230	400	4950	15,38	1,06 A
RU0100690032 [*]	230V-50/60Hz Blow.	230	400	4950	15,38	1,06 A
RU0100690041	230/400V-50/60Hz 3FN Suct.	230	400	4615	15,38	0,39 A
RU0100690042	230/400V-50/60Hz 3FN Blow.	230	400	4615	15,38	0,39 A
RU0100690051	Pred. Hydraulic. Suct. (Supp. G2)	250	400	7050	15,38	1,5 kW
RU0100690052	Pred. Hydraulic. Blow. (Supp. G2)	250	400	7050	15,38	1,5 kW

[*] In SINGLE PHASE models (*31/*32), ADJUSTABLE THERMOSTAT 0-90° on request.

Technical Specification

Minimum Range	Kw 12 : 60 lt
Maximum Range	Kw 32 : 200 lt





The overall dimensions and the technical characteristics are to be considered indicative, dealing with standarf products in constant evolution.

RAAL ITALIA s.r.l. Via G. Finati, 53 - 44124 Ferrara (ITA) C.F./P.IVA 01650320383
Tel: (+39) 0532.773637 Fax: (+39) 0532.776476 www.raal.it mail:info@raal.it